



Part. S0715



■ Guide rail




Length metres	Code	Weight kg/m
3	UL691892N	0,59

- Material: metal profile in anodized aluminium. Plastic profile in Polyethylene ULF (brown red).
- Standard packaging: The plastic and metal profiles are supplied disassembled.
- Min. curvature radius: 500 mm.
- Packaging: 72 metres.

Part. S0716

■ Plastic profile




Material UHMWPE	Packaging metres	Code
ULF - brown red	60	UL613833N

- Standard packaging: coil.
- Weight: 0,09 Kg/m.

Part. S0717

■ Metal profile



Metal profile material	Length metres	Code
Anodized aluminium	3	686222

- Min. curvature radius: 500 mm.
- Packaging: 60 metres.
- Weight: 0,50 Kg/m.

● Best Seller

● Standard

● On request: minimum quantity may apply. Consult our Customer Service for availability.

Item code for order = Part. + Code

• **Material:** Polyethylene UHMWPE with molecular density 5.600.000 g/mol.

Characteristics: new material Polyethylene ULF brown red (UHMWPE): reduced friction coefficient, higher wear resistance.

• **Linear expansion coefficient:** $2 \times 10^{-4} \text{ } ^\circ\text{C}^{-1}$

Calculation of thermal expansion see Technical information.

• **Operating temperature ULF - brown red:**

In air (- 40 to + 45 °C).


In hot water (+ 45 °C).

• **Polyethylene ULF is FDA approved**


Polyethylene ULF complies with the Code of Federal Regulations Title 21, § 177.1520 "Olefin Polymers" of the Food and Drug Administration (FDA) of April 1, 2008.

• **Accessories:** see Guide - Rail Clamps


Part./Art./Réf.
S0216 - S0903




Part./Art./Réf.
S0275




Part./Art./Réf.
S0215




Part./Art./Réf.
S0211 - S0446



Part./Art./Réf.
S0210 - S0210P



Part./Art./Réf.
S0217



Part./Art./Réf.
S0213

