
# **Close Coupled Coupling AY Series - Form-Flex®**

## **Positioning Applications - Double Flex Short Spacer**

The AY series is specifically designed for positioning applications where a servo or stepper drive is C flange mounted and connects to a ball screw. The AY accommodates the small amounts of angular and parallel misalignment with an absolute minimum size package, zero backlash and high torsional stiffness. The AY is made up of two hubs, a steel spacer block, two stainless steel disc packs and AY hardware. The coupling must be installed as an assembled unit. The spacer is not service removable.



Size	Max Bore				Dimensions (in)*							
	AJ		AZ				DBSE					Disc
	(in)	(mm)	(in)	(mm)	Α	В	D** Min	D Max	F	G	н	Pack I.D.**
5	0.875	22	1.19	30	2.65	2.85	0.49	0.85	1.00	0.24	1.30	1.00
10	1.250	33	1.63	43	3.19	2.91	0.50	0.91	1.00	0.27	1.80	1.17
15	1.375	36	1.75	48	3.65	3.33	0.56	1.07	1.13	0.32	2.00	1.28
20	1.688	46	2.13	58	4.08	3.76	0.56	1.12	1.32	0.34	2.40	1.65
25	2.000	53	2.56	68	4.95	4.77	0.87	1.53	1.62	0.45	2.80	1.78

<sup>\*</sup> Dimension shown are for AJ hubs unless otherwise specified.

<sup>\*\*</sup> Shaft O.D. must be less than Disc Pack I.D. in order to extend shafts into the coupling to meet D Min dimensions.

		Rated	Peak O/L				Misalignment Capacity		
Size	HP/100 RPM	Torque (lb-in)	Torque (lb-in)	Max RPM	Weight (lbs) (1)	WR <sup>2</sup> (lb-in <sup>2</sup> ) (1)	Axial (+/-in)	Angular (Degrees/Disc Pack)	
5	0.48	300	600	8,500	1.64	1.24	0.030		
10	1.27	800	1,600	7,500	2.68	3.08	0.040		
15	2.5	1,575	3,150	6,700	4.23	6.41	0.042	1°	
20	3.49	2,200	4,400	6,200	5.49	9.92	0.055		
25	6.03	3,800	7,600	5,500	9.78	27.6	0.060		

<sup>1)</sup> Weight and WR2 values shown are for AJ hubs at max inch bore.

#### STANDARD MATERIALS (CLASS A)

HUBS - CARBON STEEL
SPACER - CARBON STEEL
HARDWARE - ALLOY STEEL
DISC PACK - STAINLESS STEEL

#### **ORDERING**

AY SERIES COUPLINGS ARE SOLD AS COMPONENTS COUPLINGS CONSIST OF:

- 2 HUBS Example (AJ25A x 1-3/4")
- 1 SPACER SUB-ASSEMBLY Example (AY25SAA)

### **MATERIAL / FINISH OPTIONS**

CLASS A - Mild steel hubs and spacer, alloy steel hardware, 300 series stainless steel disc pack

CLASS B - Zinc plated steel hubs, and spacer, alloy steel hardware, 300 series stainless steel disc pack